

#### **Focused**

Compressed air leaks are a senseless waste of energy. Find and fix them fast with SDT LEAKChecker; an ultrasound solution focused on reducing waste and saving you money.

## **Simple**

LEAKChecker is so easy to use. Simply open the box, switch it on, and start finding leaks. Enjoy crystal-clear sound in the headset and a vibrant colour display. LEAKChecker makes leak surveying fun again.

### **Affordable**

Air leaks are an expensive problem... and LEAKChecker is the affordable solution. Built with SDT quality, it's offered at a price that will leave you speechless.

Create leak reports fast with





**Download for free today** 







# **LEAKChecker Features**

## **Description**

LEAKChecker is an ultrasound solution designed to find compressed air and vacuum leaks in noisy environments. Measure the level of the leak with LEAKChecker, then estimate its cost impact with the LEAKReporter App, available for free on the App store.

LEAKChecker comes with a 16mm diameter replaceable ultrasound sensor.

## **Kit Contents**

- LEAKChecker
- Headphones
- USB Cable
- Carrying case



| General   |   |
|---|---|
| Function  | Ultrasound measurement device   |
| Display   | 160x128 pixels Color OLED   |
| Keyboard  | 5 function keys   |
| Measuring range                                       | -6 to 99.9 dBμV (reference 0 dB = 1 μV) (resolution 0.1 dBμV)   |
| Measurement bandwidth                                 | 35 to 42 kHz  |
| Signal amplification                                  | +30 to +102 in steps of 6 dB  |
| Response time   | <9 milliseconds   |
| Minimum sensitivity                                   | -31dB (@40 kHz, 0 dB-1 V/µbar) Equal to a flow rate up to 10 <sup>-3</sup> std. cm <sup>3</sup> /sec. |
| Environmental   |   |
| Operating temperature range                           | -10 to +50 °C  14 to 122°F  |
| IP rating   | IP42  |
| Mechanical  |   |
| Housing material and weight                           | ABS, 200g   7.05oz  |
| Dimensions housing                                    | 158x59x38.5 mm  6.22"x2.32"x1.51"   |
| Flexible rod length (includes replaceable sensor tip) | 445 mm  17.51"  |
| Power   |   |
| Battery   | 2 AA batteries  |
| Autonomy  | 4 hours   |
| Audio   |   |
| Amplification   | -24 to 0 dB in steps of 6 dB  |
| Maximum output  | +83dB SPL with 25dB NRR Peltor HQ SDT headset   |

# The SDT Checkers Range:

Ultrasound detectors that solve four major reliability problems.

**LEAKChecker:** Find compressed air and vacuum leaks **TRAPChecker:** Assess the condition of traps and valves

**LUBEChecker:** Optimize bearing lubrication

**TIGHTChecker:** Verify the tightness of closed volumes









#### SDT: Leader in ultrasound detection

SDT provides ultrasound solutions that help our customers gain a better understanding about the health of their factory. We help them predict failures, control energy costs, and improve product quality while contributing to the overall reliability of their assets.



#### SDT International s.a./n.v.

Bd de l'Humanité, 415 B-1190 Brussels (Belgium) Tel: +32(0)2-332 32 25 Email: info@sdt.be

#### **SDT North America**

1532 Ontario Street Cobourg, ON (Canada) Toll free: 1-800-667-5325 Int'l direct: 1-905-377-1313 Email: info@sdthearmore.com



Edificio Trovador. Plz. Antonio Beltrán 1 · P. 6 · Of. I · 50002 Zaragoza +34 976 200 969 | preditec.com | info@preditec.com Madrid | Barcelona | Zaragoza | Lisboa | Lima | Quito | Texas